

DRYLAM

SELECTION ♦ SOLUTIONS ♦ SIMPLICITY

LPP6512 & LPP1112 Heated Roller Laminators



INTRODUCING the Fujipla LPP Series Heated Roller Laminators.

Economical yet reliable introductory grade wide format laminators in 25" and 43" widths. All metal construction for durability, with heated lamination nip rollers for scratch free laminations. Digital temperature control from room temperature to 270°F allows you to run thermal films and with optional release liner rewinder, PSA/Cold laminates.

www.drylam.com • P: 888-633-1973 • F: 866-473-0534
23220 W 84th Street • Shawnee, KS 66227

LPP6512 & LPP1112 Heated Roller Laminators

DRYLAM

SELECTION ♦ SOLUTIONS ♦ SIMPLICITY

LPP6512 & LPP1112 Heated Roller Laminators

Safety Features:

- Emergency Shutoff button on top rear corner of the machine (LPP1112 only)
- Magnetic safety switches on feed tray and roller guard shield
- Removable roller guard shield



Key Features:

- Foot pedal web advance included
- Heavy duty roller stand included
- Digital temperature readout
- Optional liner rewinder available for use of PSA films
- Energy saving standby mode
- Heated rollers for scratch free laminations



FUJILAM

Model:	LPP6512 Laminator	LPP1112 Laminator
Maximum Laminating Width:	25 inches	43 inches
Laminating Film Thickness:	1.2 - 5 mil	1.2 - 5 mil
Film Types:	Thermal (PSA with optional liner rewinder)	Thermal (PSA with optional liner rewinder)
Heated Rollers Upper and Lower:	Room Temperature to 270° F	Room Temperature to 270° F
Speed:	0 - 6 feet per minute	0 - 6 feet per minute
Unwind Mandrels Upper and Lower:	1" mandrels with 2.25" and 3" adapters	1" mandrels with 2.25" and 3" adapters
Gross Weight Laminator:	169 lbs	196 lbs
Stand Included (weight):	60 lbs	90 lbs
Power Requirements:	230VAC Single Phase	230VAC Single Phase
Wattage:	2000	3000
Plug Type:	Nema N6-30P	Nema N6-30P