

DRY-LAM

SELECTION ♦ SOLUTIONS ♦ SIMPLICITY

LPV1200 DUO System



FUJIFILM

DRY-LAM takes lamination of On-Demand Digital Prints to a new level.

The **Drylam Duo System** takes care of all your wide format laminating needs. The system allows you to choose the best type of laminate for your application. Run cost effective thermal laminates on most paper stocks and porous materials. Pressure sensitive cold laminates are perfect for non porous synthetic stocks, or stocks that are heat sensitive, including applications such as floor graphics, decals, and signage.

www.drylam.com • P: 888-633-1973 • F: 866-473-0534
23220 W 84th Street • Shawnee, KS 66227

LPV1200 DUO System

LPV1200 DUO System



Safety Features:

- Emergency Shutoff buttons on top rear corners of the machine
- Nip area sensors stop roller advancement if tripped
- Nip area safety shield swings up for easy threading and cleaning



Key Features:

- Foot pedal web advance included
- Heavy duty roller stand included
- Mechanical actuated roller pressure gaps up to 1 inch
- Mandrels marked at 38" and 43" for easy film alignment
- Digital temperature readout for top and bottom nip rollers
- Run thermal or PSA Films



LPV1200	Model:	LPV1200 DUO System
	Maximum Laminating Width:	47 inches
	Maximum Laminating Thickness:	1 inch
	Laminating Film Thickness:	1.2 - 10 mil
	Film Types:	PSA and Thermal
	Temperature Range:	Room Temperature to 270° F
	Dual Temperature Control:	Upper and Lower
	Heated Rollers Upper and Lower:	Room Temperature to 270° F
	Speed:	0 - 12 feet per minute
	Unwind Mandrels Upper and Lower:	3" core
	PSA Liner take up Mandrel top:	3" core
	Gross Weight Laminator:	595 lbs
	Stand Included (weight):	100 lbs
	Power Requirements:	230VAC Single Phase
	Wattage:	4000
Plug Type:	Nema NP-30P	